

One Piece Fixing Tie with Arrowhead

Features and Benefits

The arrowhead is simply pushed through the panel and locks into place, the design of the arrowhead (without 'legs') ensures that the minimum amount of space is used, and yet offers a firm, secure fixing.

Application

The arrowhead design allows these ties to be used in areas with limited space.



The arrowhead design allows these ties to be used in areas with limited space.

Material Data

RoHS	Material	Polyamide 6.6 Heat Stabilised (PA66HS)
	Colour	Black (BK)
	Operating Temperature	-40°C to +105°C Continuous, (+145°C for 500 h)
	Flammability	UL94 V2
	HF (halogenfree)	

Material Data

RoHS	Material	Polyamide 6.6 (PA66)
	Colour	Natural (NA)
	Operating Temperature	-40°C to +85°C Continuous, (+105°C for 500 h)
	Flammability	UL94 V2
	HF (halogenfree)	

Application Tool	Registration Numbers
MK3SP	1
MK3PNSP2MK7P	2
MK7	3
MK7HT	4
MK20	5
MK6	6
MK9P, MK6PN	7
MK9	8
MK9HT	9
MK21	10

For more information on Application Tools please refer to Page 2/10.



T30RSF



T50RSF



T50RSF(U)

Technical Table

Code	Length (L)	Width (W)	Bundle Ø max.	Min. Tensile Strength (N)	Hole Ø	Panel Thickness min.	Panel Thickness max.	Material	Colour	Application Tool
T30RSF(U)	161	3.6	31.8	135	4.76-5.59	0.9	2.36	PA66	Natural (NT)	1-3, 5
T30RSF(U)	161	3.6	31	135	4.8-5.6	0.9	2.3	PA66HS	Black (BK)	1-3, 5
T50RSF(E)	210	4.6	50	225	6.2-6.4	2.9	3.1	PA66	Natural (NT)	1-3, 5
T50RSF(E)	210	4.6	50	225	6.2-6.4	2.9	3.1	PA66	Black (BK)	1-3, 5

All dimensions in mm. Subject to technical changes.



Please Note for Product Specific Approvals please refer to Appendix.