

## HT Heavy Duty Lugs

Technical Table

Cable Size (mm <sup>2</sup> )	Stud (mm)	Code	Dimensions (mm)						
			Barrel				Spade		
			A ID	B OD	t Thickness	C Length	D Length	E Hole to End	W Width
70	8	HT708	11.7	15.0	1.65	21	20	10	21
	10	HT7010	↓	↓	↓	↓	26	11	22
	12	HT7012	↓	↓	↓	↓	28	12	22
	16	HT7016	↓	↓	↓	22	32	14	28
	20	HT7020	↓	↓	↓	22	34	15	30
95	8	HT958	13.5	17.4	1.95	23	24	10	25
	10	HT9510	↓	↓	↓	↓	26	13	26
	12	HT9512	↓	↓	↓	↓	28	13	26
	16	HT9516	↓	↓	↓	↓	32	14	28
	20	HT9520	↓	↓	↓	↓	36	16	30
120	10	HT12010	15.5	19.8	2.15	26	26	12	27
	12	HT12012	↓	↓	↓	↓	28	12	28
	16	HT12016	↓	↓	↓	↓	32	14	30
	20	HT12020	↓	↓	↓	↓	36	16	32
150	10	HT15010	17.0	22.0	2.50	27	31	12	31
	12	HT15012	↓	↓	↓	↓	33	16	32
	16	HT15016	↓	↓	↓	↓	35	↓	↓
	20	HT15020	↓	↓	↓	↓	36	↓	↓
185	10	HT18510	19.0	24.4	2.70	29	29	13	34
	12	HT18512	↓	↓	↓	↓	31	16	34
	16	HT18516	↓	↓	↓	↓	34	16	36
	20	HT18520	↓	↓	↓	↓	40	19	36
240	10	HT24010	21.5	27.7	3.10	33	38	16	40
	12	HT24012	↓	↓	↓	↓	↓	↓	↓
	16	HT24016	↓	↓	↓	↓	↓	↓	↓

## HT Heavy Duty Ferrules



Random samples submitted to the SABS complied with SABS IEC1238-1:1993 and the relevant test report is freely available upon request.

The test report relates only to the items submitted for the actual test and it furnishes or implies no guarantee whatsoever in respect of similar items that have not been tested. The performance of the test and the issue of the test report do not imply approval by the SABS of the quality and/or performance of the items that have been tested but signifies that the items tested met the requirements of: SABS IEC1238-1:1993 / RCC NO: 0902175.

Technical Table

Cable Size (mm <sup>2</sup> )	Code	Dimensions		
		A I.D	B OD	L Length
1.5	HT1F	1.9	3.8	12
2.5	HT2F	2.4	3.9	15
4	HT4F	2.8	4.7	15
6	HT6F	3.4	5.3	15
10	HT10F	4.4	6.3	22
16	HT16F	5.5	7.6	22
25	HT25F	6.9	9.0	24
35	HT35F	8.2	10.7	27
50	HT50F	10.0	12.8	30
70	HT70F	11.7	15.0	34
95	HT95F	13.5	17.4	38
120	HT120F	15.5	19.8	42
150	HT150F	17.0	22.0	48
185	HT185F	19.0	24.4	53
240	HT240F	21.5	27.7	60