

Selection Guide

	T609	TBM0030	T2600	TBM126	T98	T2600	T2312	T2026	TBM116	TBM118	TBM135	T223	TCM02	T2102	TBM061	TBM062	T8056	T2138	T2606	TBM162	T2608	TBM155	TCM03	TA300	T500T	T1000
AC Current	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
DC Current													•	•	•	•	•	•	•	•	•					
AC Voltage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
DC Voltage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Resistance		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Frequency		•	•	•			•	•	•	•	•		•		•	•	•	•	•	•	•	•	•			
Capacitance		•	•	•			•	•	•	•	•		•		•	•	•	•	•	•	•	•	•			
Temperature				•	•								•									•			•	
Power																						•				
Analogue Bar Graph													•	•												
True Rms								•	•	•	•					•			•	•	•	•				
Peak Hold															•	•										
Data Hold	•		•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
MinMax		•		•																						
Continuity Buzzer		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Auto Null (leads)		•																								
Leakage Current																							•			
Max Current (A)	200	600	200	600	1000	1000	1000	1000	1000	2000	1000	100	200	400	600	600	1000	1000	1000	1000	2000	1000	40	300	600	1000
Jaw Size (mm)	21	26	12	26	42	60	40	40	45	45	45	125	23	28	30	30	42	40	40	50	57	45	30	34	34	52
Analogue Display																								•	•	•
Digital Display	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Backlight			•		•		•	•								•	•	•	•	•	•	•				

NEW

T1805 Analogue

- Large display
- Rugged construction
- Taut band movement
- 2 & 3 wire tester



CAT III 300V IEC61010-1

Meter Supplied With Certificate of Conformance



Technical Specification

Measuring Ranges	Resistance: 10, 100, 1,000Ω
Earth Voltage	30V AC (5KΩ/V)
Measuring System	Resistance: (Constant current inverter 820Hz approx., 2 mA) Voltage: rectifier type 0 - 30 VAC, 40 - 500 Hz
Withstand Voltage	1,500V AC (one minute)
Accuracy	
Resistance	±2.5% of full scale
Voltage	±1% of full scale

Model Specification

Accessories	Test Leads, Earth Spikes Carry Strap
Dimensions (mm)	170(L) x 165(W) x 92(H)
Power Source	8 x 1.5V AA Batteries
Weight	1000g

Test Leads Lengths

Red -	1,2 & 15 meters
Yellow -	10 meters
Green -	5 meters



T1820 Digital

- Rugged construction
- Earth voltage detection
- Auto off
- Data Hold
- 2 & 3 Wire Testing



CAT III 300V IEC61010-1

Meter Supplied With Certificate of Conformance



Technical Specification

Measuring Ranges	Resistance: 20,200,2kΩ
Earth Voltage	200V AC (40 - 500hz)
Measuring System	Earth resistance by constant current inverter, 400Hz, 2mA Approx
Withstand Voltage	1,500V AC (one minute)
Accuracy	
Resistance	±2% rdg + 2 Digit
Voltage	±1% rdg + 2 Digit

Model Specification

Accessories	Test Leads, Earth Spikes Carry Strap
Dimensions (mm)	170(L) x 165(W) x 92(H)
Power Source	8 x 1.5V AA Batteries
Weight	1000g

Test Leads Lengths

Red -	1,2 & 15 meters
Yellow -	10 meters
Green -	5 meters